

RDA-C

'Clip-on' Self-levelling Adjustable Decking Pedestal

Overview

Self-levelling adjustable decking pedestal with 'click head' available in a range of height build-ups, compatible with DS joist, which clicks into place on pedestal head.

- Aluminium joists can be clicked into place
- Multi-directional head allows for multiple configurations, single joists, double joists and perpendicular joist interfaces
- Ball and socket joint creates a free moving captive head
- Provides slope correction of up to 10.5% (6°)
- Millimetre perfect height adjustment
- Height extension collar raises the total height by 100mm
- Holes in the base allow drainage and fixing to substrates
- Wide base protects the roof membrane
- Base can be cut down to allow for placement against the wall abutment



Performance

| | |
|----------------------------|--|
| Materials | Polypropylene (recyclable) |
| Biological/chemical | Resistant to moulds, algae, alkali, bitumen |
| Compression | 2100kg (certified compression data available on request) |
| Base dimensions | 210mm/220mm |
| Head dimensions | 115x130mm |
| Bearer capacity | Single or double DS aluminium joist |
| Working temperature | -40°C to 120°C |

Got questions?

Speak to one of our expert advisors

Visit www.rynogroup.co.uk or call us today on **+44 (0)203 967 3500** or reach out on sales@rynogroup.co.uk.

Sizes

| Code | Adjustable height range |
|----------------|-------------------------|
| RDA-1C | 40-56mm |
| RDA-2C | 50-70mm |
| RDA-3C | 70-110m |
| RDA-4C | 110-160mm |
| RDA-5C | 150-210mm |
| RDA-6C | 200-300mm |
| RDA-7C | 300-400mm |
| RDA-8C | 400-500mm |
| RDA-9C | 500-600mm |
| RDA-10C | 600-700mm |
| RDA-11C | 700-800mm |
| RDA-12C | 800-900mm |
| RDA-13C | 900-1000mm |


Accessories



Base shock pads

Base shock-absorbent membrane pads can be installed under the pedestal/support base to enhance acoustic properties, or to provide additional protection to the waterproof system.

Compatible Systems

 Deck
TerraSmart™ Composite

Wood-plastic composite decking system for outdoor spaces

 Pave
TerraSmart™ Rail

Premium, versatile paving system for waterproofed substrates, **where non-combustibility isn't required**

Got questions?

Speak to one of our expert advisors

Visit www.rynogroup.co.uk or call us today on **+44 (0)203 967 3500** or reach out on sales@rynogroup.co.uk.