

RPF-LH

Low-height Adjustable Paving Support

Overview

The RPF-LH can be used to support paving slabs from a void height of 10–22mm and is fully height adjustable using the two adjustable rings.

- Spacer tabs provide consistent spacing between slabs.
- The adjustable thread allows millimetre perfect adjustment
- 10-year warranty



Performance

Material	Polypropylene (recyclable)
Biological/chemical	Resistant to moulds, algae, alkali, bitumen
Base diameter	155mm
Spacer tab thickness	2mm / 4mm (standard)
Pack size	Packs of 25

Sizes

Code	Adjustable height range	Spacer tab thickness	Product weight
RPF-LH-1	10-16mm	2mm/4mm	0.9kg ea
RPF-LH-2	16-22mm	2mm/4mm	0.13kg ea

Accessories



Edge spring clip

The edge spring clip fits on top of paving supports around the periphery of paved areas to ensure uniform spacing against wall abutments, helping ensure rapid drainage. By tensioning the tile bed, it counteracts creepage and movement.



Head shock pads

Head shock-absorbent gaskets fit on top of the paving supports, cushioning tiles and removing the possibility for grit to cause grinding between tile and pedestal head.



Base shock pads

Base shock-absorbent membrane pads can be installed under the pedestal/support base to enhance acoustic properties, or to provide additional protection to the waterproof system.

Compatible Systems



TerraSmart™ Pedestal

Straightforward, robust paving system for waterproofed substrates, **where non-combustibility isn't required**

Got questions?

Speak to one of our expert advisors

Visit www.rynogroup.co.uk or call us today on **+44 (0)203 967 3500** or reach out on sales@rynogroup.co.uk.