

RPF

Fixed Head Adjustable Paving Pedestal

Overview

The RPF fixed-head adjustable paving pedestal is designed to support all types of calibrated paving.

- Spacer tabs provide consistent spacing between slabs. ‘Snap off’ design allows for easy removal.
- Adjustable thread allows millimetre perfect adjustment
- Wide base evenly spreads the load, protecting membranes
- Drainage holes prevent moisture build-up on base



Performance

Material	Polypropylene (recyclable)
Biological/chemical	Resistant to moulds, algae, alkali, bitumen
Compression	1000kg
Base diameter	200mm
Head diameter	120mm
Spacer tab thickness	2mm / 4mm (standard) / 6mm / 8mm / 10mm
Working temperature	-40°C to 120°C
Reaction to fire	B _{Roof} (t ₄) in accordance with EN 13505:2018 when used as part of the complete TerraSmart Pedestal System

Sizes

Code	Adjustable height range
RPF-1	22-35mm
RPF-2	35-55mm
RPF-3	55-95mm
RPF-4	95-165mm
RPF-5	165-235mm
RPF-6	200-270mm
RPF-7	260-340mm
RPF-8	305-375mm
RPF-9	365-445mm
RPF-10	410-480mm
RPF-11	470-550mm

Accessories



Edge spring clip

The edge spring clip fits on top of paving supports around the periphery of paved areas to ensure uniform spacing against wall abutments, helping ensure rapid drainage. By tensioning the tile bed, it counteracts creepage and movement.



Head shock pads


Head shock-absorbent gaskets fit on top of the paving supports, cushioning tiles and removing the possibility for grit to cause grinding between tile and pedestal head.



Base shock pads

Base shock-absorbent membrane pads can be installed under the pedestal/support base to enhance acoustic properties, or to provide additional protection to the waterproof system.

Compatible Systems



TerraSmart™ Pedestal

Straightforward, robust paving system for waterproofed substrates, **where non-combustibility isn't required**

Got questions?

Speak to one of our expert advisors

Visit www.rynogroup.co.uk or call us today on **+44 (0)203 967 3500** or reach out on sales@rynogroup.co.uk.