

RST Aluminium Paving Support Top Rail



Overview

RST aluminium top rails form part of Ryno's Rail systems. They provide complete support for paving. They can be laid at any centre-to-centre intervals across primary rails, to cater for varied paving course widths.

The rails feature an integrated 2mm shock-absorbent gasket, a channel for paving spacers to lock into, and side flanges for robust fixing into lower primary rail.

- Continuous linear support for paving
- Shock-absorbent gasket eliminates paving grinding against aluminium
- Allows for random length paving
- Twist-lock in spacers fix into centre channel



Performance

Allowable load	Uniformly distributed >4.0kN/m ² , Concentrated 2kN
Aluminium grade	6063 T6
Biological/Chemical	Resistant to moulds algae, alkali, bitumen, UV
Reaction to fire	A1

Dimensions and Spans

Code	Height x Width	Span	Weight	Lattice system
RST27	27mm x 80mm	600mm	2.4kg/m ²	Yes
RST62	62mm x 80mm	1400mm	3.1kg/m ²	Yes

Got questions?

Visit www.rynogroup.co.uk or call us today on **+44 (0)203 967 3500** or reach out on sales@rynogroup.co.uk.

Accessories



Paving Spacers

T, Straight and Cross spacers inserted to the rail providing uniform spacing between slabs



Edge and Side Stops

Attached to the RST on the edges to secure pavers in place and minimise movement



Joist screw

Hex washer head screw 4.8X19mm

Compatible Systems



TerraSmart®
Rail Paving System

Premium, versatile paving system for waterproofed substrates



BalcaSmart®
Rail Paving System

Premium, versatile paving system for waterproofed substrates

TerraSmart®
Rail Paving System

Premium, versatile paving system for waterproofed substrates, **where non-combustibility isn't required**