

# RDA-C

## 'Clip-on' Self-levelling Adjustable Decking Pedestal

### Overview

Self-levelling adjustable decking pedestal with 'click head' available in a range of height build-ups, compatible with DS joist, which clicks into place on pedestal head.

- Aluminium joists can be clicked into place
- Multi-directional head allows for multiple configurations, single joists, double joists and perpendicular joist interfaces
- Ball and socket joint creates a free moving captive head
- Provides slope correction of up to 10.5% (6°)
- Millimetre perfect height adjustment
- Height extension collar raises the total height by 100mm
- Holes in the base allow drainage and fixing to substrates
- Wide base protects the roof membrane
- Base can be cut down to allow for placement against the wall abutment



### Performance

<b>Materials</b>	Polypropylene (recyclable)
<b>Biological/chemical</b>	Resistant to moulds, algae, alkali, bitumen
<b>Compression</b>	2100kg (certified compression data available on request)
<b>Base dimensions</b>	210mm/220mm
<b>Head dimensions</b>	115x130mm
<b>Bearer capacity</b>	Single or double DS aluminium joist
<b>Working temperature</b>	-40°C to 120°C

**Got questions?**

**Speak to one of our expert advisors**

Visit [www.rynogroup.co.uk](http://www.rynogroup.co.uk) or call us today on **+44 (0)203 967 3500** or reach out on [sales@rynogroup.co.uk](mailto:sales@rynogroup.co.uk).

## Sizes

Code	Adjustable height range
RDA-1C	40-56mm
RDA-2C	50-70mm
RDA-3C	70-110m
RDA-4C	110-160mm
RDA-5C	150-210mm
RDA-6C	200-300mm
RDA-7C	300-400mm
RDA-8C	400-500mm
RDA-9C	500-600mm
RDA-10C	600-700mm
RDA-11C	700-800mm
RDA-12C	800-900mm
RDA-13C	900-1000mm

## Accessories



### Base shock pads

Base shock-absorbent membrane pads can be installed under the pedestal/support base to enhance acoustic properties, or to provide additional protection to the waterproof system.

## Compatible Systems

### TerraSmart®

Composite Decking System

Wood-plastic composite decking system for outdoor spaces

### TerraSmart®

Rail Paving System

Premium, versatile paving system for waterproofed substrates, **where non-combustibility isn't required**

## Got questions?

### Speak to one of our expert advisors

Visit [www.rynogroup.co.uk](http://www.rynogroup.co.uk) or call us today on **+44 (0)203 967 3500** or reach out on [sales@rynogroup.co.uk](mailto:sales@rynogroup.co.uk).